



Idaxis® SecurePIV Smart Card Readers

- 4 Innovative Models to Match all Needs
- Fastest ISO 7816 Reader⁽¹⁾
- TAA Compliant
- Custom Logo⁽²⁾

SecurePIV Pro USB



SecurePIV Pro USB-C



SecurePIV mini USB



SecurePIV mini USB-C





Idaxis® SecurePIV Tech Specs

Physical Characteristics

SecurePIV Pro: 66.0mm (L) x 66.0mm (W) x 9.3mm (H) - 48g
SecurePIV mini: 58.0mm (L) x 19.0mm (W) x 11.8mm (H) - 11g
Casing: Black ABS
Supported Card Size: ID-1 (Full size)

Contact Smart Card Interface

Standard: ISO/IEC 7816 Part 1/2/3/4
Protocol:T=0, T=1, Memory card
Supported Card Types: ISO7816 Class A/ B/ C (5V/ 3V/ 1.8V)
Power: 55mA in Class A/ B/ C
Speed: 9.6 - 826 Kbps
Clock Frequency: 4.8 - 16MHz
Card Connector: Minimum 100,000 insertion cycles

USB Interface

USB 2.0 Full Speed (12 Mbps)
Operating Power Consumption: <100 mA
Standby Power Consumption: <2mA
"SecurePIV Pro USB" and "SecurePIV mini USB" connector: USB-A
"SecurePIV Pro USB-C" and "SecurePIV mini USB-C" connector: USB-C
"SecurePIV Pro USB" and "SecurePIV Pro USB-C" wire length: 1m
SecurePIV mini connection: no wire, direct connection to device

Supported OS

Windows® 7 SP1 and above
Linux®
Mac OS® 10.12 and above
Android™ 6.0 and above

Compliance & Certifications

ISO/IEC7816 and EMV 2011 Ver 4.3 Level 1
USB 2.0 Full Speed
CCID & Microsoft® WHQL
Regulatory: EN 60950/IEC 60950, CE, FCC, VCCI, RoHS3, REACH

US Federal Government

TAA Compliant
Compatible with CAC, PIV, PIV-i, TWIC smart cards and others

Part Numbers & UPC

"SecurePIV Pro USB"	P/N: TLP225A	UPC: 786899878189
"SecurePIV Pro USB-C"	P/N: TLP225C	UPC: 786899878196
"SecurePIV mini USB"	P/N: TLP125A	UPC: 786899878202
"SecurePIV mini USB-C"	P/N: TLP125C	UPC: 786899878219

Idaxis®
1001 Fillmore Street, Suite 3157
Arlington, Virginia 22201, USA
www.idaxis.com
info@idaxis.com

© 2022 Idaxis®. All rights reserved. Actual data may differ. Document may be updated without prior notification. All brands and trademarks belong to their respective holders. Idaxis® is a registered trademark in the United States.
(1) Speeds up to 826 kps with TA1=17
(2) With a minimum order of 2000 units